

[View](#) [Sync](#) [Diff Revs](#) [Diff vs Client File](#) [Describe Changelist](#) [Help](#)

Revision	File Name	Changelist	Date	Description
----------	-----------	------------	------	-------------

1	//depot/m...	2357	2000/01/14	Merge in calendar sync changes from Continuous.
---	--------------	------	------------	---

```

5  #include "CalSyncState.h"
   #include "debug.h"
   #include "globals.h"
   #include "sha.h"

   static char * BlackBerryFolderName      = "BlackBerryHandheldInfo";
   static char * BlackBerryCalStateFolderName = "BlackBerryCalSyncState";
   static char * MSG_CLASS_CAL_SYNC       = "RIM.BlackBerry.CalSync";
   static char * MSG_CLASS_SYNC_TIMESTAMP = "RIM.BlackBerry.SyncTimestamp";

10  // Base tag for new properties
   unsigned long const  BASE_PM_ID      = 0x6200;

   //////////////////////////////////////
15  // Constructor/Destructor
   //////////////////////////////////////

   // *** CalSyncState ***
   // Purpose: Constructor for the CalSyncState class.
   // Parameters: [IN] pMailbox = pointer to user mailbox object.
   //             [IN] lpStore = pointer to Exchange message store object.
   //             [IN] lpCalendarFolder = pointer to user's Calendar folder.
   // Returns:
   //
25  CalSyncState::CalSyncState( MAPIMailbox *pMailbox, LPMDB lpStore, LPMAPIFOLDER lpCalendarFolder )
   {
       // Initialize member variables
       m_pMDB = lpStore;
       m_pMailbox = pMailbox;
       m_pCalendarFolder = lpCalendarFolder;
       m_pStateFolder = 0;

35       // Initialize property tags used to save state information into message
       PR_RIM_SYNC_ENTRYID      = PROP_TAG(PT_BINARY, (BASE_PM_ID));
       PR_RIM_SYNC_SOURCE_KEY   = PROP_TAG(PT_BINARY, (BASE_PM_ID + 0x0001));
       PR_RIM_SYNC_INSTANCE_DATE = PROP_TAG(PT_SYSTIME, (BASE_PM_ID + 0x0002));
       PR_RIM_SYNC_REF_ID       = PROP_TAG(PT_LONG, (BASE_PM_ID + 0x0003));
       PR_RIM_SYNC_PARENT_REF_ID = PROP_TAG(PT_LONG, (BASE_PM_ID + 0x0004));
       PR_RIM_SYNC_LAST_MODIFIED = PROP_TAG(PT_SYSTIME, (BASE_PM_ID + 0x0005));
       PR_RIM_SYNC_DEVICE_SEQNUM = PROP_TAG(PT_LONG, (BASE_PM_ID + 0x0006));
       PR_RIM_SYNC_DESKTOP_SEQNUM = PROP_TAG(PT_LONG, (BASE_PM_ID + 0x0007));
       PR_RIM_SYNC_DELETE_IN_PROGRESS = PROP_TAG(PT_BOOLEAN, (BASE_PM_ID + 0x0008));
       PR_RIM_SYNC_MODIFY_IN_PROGRESS = PROP_TAG(PT_BOOLEAN, (BASE_PM_ID + 0x0009));

```